


Satellites Mixer Showers

hp mixing unit



IMPORTANT NOTICE

In commercial premises metallic surfaces e.g. metal ceiling panels, metal ducting and metal insulating materials may block wireless transmissions from the remote control panel and prevent correct operation of the shower.

Please contact Triton's special advisory service on 0844 980 0730 for guidance on commercial installations and if necessary make the arrangements for a site survey.



Operating Features

- Versatile and easy to install
- Can be installed in a loft space, an airing cupboard or under a bath
- Can be mounted horizontally or vertically. When mounted vertically the unit must be positioned so that the outlet is on the top left hand side of the unit
- In line isolating valves are incorporated into the push fit connections


Finish	
High pressure mixing unit and sirona panel	
Code	SATMIXSIR-HP

Temperature Control	Thermostatic to within 2°C
Inlet Connection	15mm push fit supplied with unit
Water Entry Points	Side exposed
Cable Entry Points	Pre-wired
Outlet Connection	15mm push fit supplied with unit
Plumbing System	High pressure only
Minimum Running Pressure/Flow	1 Bar @ 8 l/min
Maximum Running Pressure	5 Bar
Maximum Static Pressure	10 Bar
Surface Mounted Only	
Approvals	BEAB
Guarantee	5 years



Satellites Mixer Showers

lp mixing unit



IMPORTANT NOTICE

In commercial premises metallic surfaces e.g. metal ceiling panels, metal ducting and metal insulating materials may block wireless transmissions from the remote control panel and prevent correct operation of the shower.

Please contact Triton's special advisory service on 0844 980 0730 for guidance on commercial installations and if necessary make the arrangements for a site survey.



Temperature Control	Thermostatic to within 2°C
Inlet Connection	15mm push fit supplied with unit
Water Entry Points	Side external
Cable Entry Points	Pre-wired
Outlet Connection	15mm push fit supplied with unit
Plumbing System	Low pressure gravity
Minimum Head Pressure/Flow	100mm
Maximum Head Pressure	10m (1 Bar)
Maximum Static Pressure	10m (1 Bar)
Approvals	BEAB
Guarantee	5 years

Operating Features

- Versatile and easy to install
- Can be installed in a loft space, an airing cupboard or under a bath
- Can be mounted horizontally or vertically. When mounted vertically the unit must be positioned so that the outlet is on the top left hand side of the unit
- In line isolating valves are incorporated into the push fit connections
- The unit incorporates two pumps therefore removing the need to install a separate twin impeller booster pump


Finish

Low pressure mixing unit and sirona panel

Code SATMIXSIR-LP

Satellites Mixer Showers

sirona panel



Operating Features

- The sirona control panel can be used with either the lp or hp mixing unit and located upto 10 metres away
- Warm up feature
- Temperature control
- Separate flow increase and decrease buttons
- Start/stop button
- Led indicator
- Battery: alkaline 2 x aaa

Dip switch	Low pressure settings	High pressure settings
1 on	Run time set @10 mins	Run time set @10 mins
1 off	Run time set @20 mins	Run time set @20 mins
2 on	Temp range 35-41°C	Temp range 35-41°C
2 off	Temp range 35-47°C	Temp range 35-47°C
3 on	Eco mode set to on	Eco mode set to 'on' if dip 4 set to 'off'
3 off	Full flow control	Full flow control if dip 4 set to 'off'
4 on	Commissioning	Flow set at number 10 (combi flow)
4 off	Normal operation	Normal operation

Satellites Mixer Showers

cyrene kit

digital showers



Operating Features

- Attaches to ceiling
- Single spray pattern

Finish	Code
Satin/Chrome	KITSATCYR