



LAPPATO PORCELAIN TILES



WHAT IT'S FOR

- Protects the surface from underfoot dirt and heavy wear.
- Restores sheen by increasing the material's surface shine.
- Makes ordinary maintenance of lappato porcelain tiles easier.
- Penetrates deep down, protecting the material from water and oily stains. The protection reaches maximum effectiveness after 24 hours.

ADVANTAGES

- Specific product for all kinds of lappato porcelain tiles.
- The protection does not form a film and allows the surface to breathe.
- Protection is permanent with no need for further application of the product.
- Ready to use.
- Highly resistant to traffic and maintenance cleaning.
- Specific product for all kinds of lappato porcelain tiles.
- Does not yellow, UV resistant. High coverage.
- The product becomes an integral part of the material without altering its appearance. (Min.Dec. No. 236 of 14/06/1989 and ASTM C 1028-2007).

HOW TO USE IT

No dilution required: ready to use.

Application for new installations:

1. Wash the floor thoroughly using **DETERDEK** (cement grout) or **FILACR10** (epoxy grout).
2. with the surface clean and dry, apply **FILAPD15** evenly on the surface (including grout joints) using a brush, sponge or fleece cloth.
3. Rub the surface with a cloth, paper or single disc machine with white disc to help with product penetration.
3. Remove any residue within 10 minutes, using a clean cotton cloth or single-disc machine fitted with a white pad. We recommend applying the product on 2-3 m² at a time.
4. The surface is ready for use after 8 hours.

Application on untreated surface to be restored:

1. Wash the floor using **FILAPS87** and/or **DETERDEK**.
2. Apply **FILAPD15** on the dry surface in the manner described above.

Suggestion:

In case of stubborn residues, rub the surface with a cloth wetted with the product until they disappear completely.

Caution:

It may enhance the colour of the material and/or grout, carry out a spot test beforehand to check for any changes in colour.

COVERAGE

With one litre:

Lappato porcelain tiles

70m²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

1-litre cans in boxes of 6.

WARNINGS

- This is a solvent-based product, we recommend airing the room during application.

COMPOSITION

A mixture of siloxanic compounds dispersed in de-aromatised hydrocarbon solvent.

LABELLING

Warning: Danger

Hazard indication:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.

Caution recommendations:

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat / sparks / open flames / hot surfaces. No smoking. Wear protective gloves / protective clothing / eye protection / face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician. Dispose of contents / container in accordance with official regulations. Contains: NAPHTHA (PETROL), HYDROTREATED HEAVY



TECHNICAL FEATURES

Appearance: liquid

Colour: colourless

Odour: typical of hydrocarbon solvent

Density: 0.978 kg/l

Flammability: 40°C

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.